

Issue No. 2	الشركة السعودية للفحص والاختبار	
Issue Date : 01/10/2020	SAUDI INSPECTION & TESTING CO. (SAITCO)	
Revision No. 3	ملحق 7 - أ: ملاحق متطلبات العملية - نتائج الاختبارات مختبر الكهرباء	
Issue Date : 05/08/2023	Appendix 7-A: LAB process REQ. TEST RESULTS -ELECTRICAL LAB	

Code of product in Lab :	C-138	   
<b>LAB DATA</b>		<b>بيانات المختبر</b>
Laboratory name	اسم المختبر	Saudi Inspection & Testing Co.(SAITCO)
Address	العنوان	1st Industrial Area, St. No.4,5,6,7-Riyadh
Country	الدولة	Saudi Arabia
<b>Client Data</b>		<b>بيانات العميل</b>
Sample Date in	تاريخ استلام العينة	8 / 4 / 2024
Date or period of tests	تاريخ / فترة الاختبار	8 / 4 / 2024
Date of report issue	تاريخ اصدار التقرير	15 / 4 / 2024
Laboratory test report number	رقم التقرير بالمختبر	E-240333
Client Name	اسم العميل	National Heater Factory for Industry
Client Address	عنوان العميل	Postal Code 14326 - Alsuli Al Mishael Dist. Riyadh , KSA
Client Reference No. / Date	مرجع العميل	8 / 4 / 2024
No of received Samples	عدد العينات المستلمة	1
<b>Sample Data</b>		<b>بيانات العينة</b>
Product description	وصف المنتج	Electric Storage Water Heater
Brand name or trademark	العلامة التجارية	NATIONAL HEATER FACTORY
Type or reference	النوع / المرجع	NH L30V
Country of Origin	بلد الصنع	SAUDI ARABIA
Manufacture Name	اسم المصنع	National Heater Factory for Industry
Manufacture Address	عنوان المصنع	Postal Code 14326 - Alsuli Al Mishael Dist. Riyadh , KSA
Products Category	تصنيف المنتج	Water Heaters - Energy Performance Requirements and Labeling
Standard / TR No.	رقم المواصفة / اللائحة	SASO 2884:2017/AMD4:2021
<b>Test case verdicts</b>		<b>حالات الحكم على نتيجة الاختبار</b>
Conformity to articles tested		<input checked="" type="checkbox"/> Yes <input type="checkbox"/> No
Test case does not apply to the test object		Not Applicable N/A
Test item does meet the requirement		Pass P
Test item does not meet the requirement		Fail F

Technical Lab supervisor / Manager



Test Report No	E-240333	Standard No:	SASO 2884
Clause	Requirement -Test	Result - Remark	Verdict

4	<b>Criteria for applying the Minimum Energy Performance Standard (MEPS)</b>		
4.1	<b>Declaration of rated values</b>	-	-
	The declaration of the rated capacity shall be expressed only in terms of liters (l) according to the following rules	-	P
	- rated capacity lower or equal to 14 liters as multiples of 1 liter	-	N/A
	- rated capacity from 15 liters as multiples of 5 liters	30L	P
	The declaration of the rated power shall be expressed only in terms of watt (W) as multiples of 50 W.	1200W	P
	The rated annual energy as a multiple of 5 kWh	570kWh	P

4.2	Determining the Minimum Performance												
4.2.1	General						-		-				
	Minimum energy performance are based on the Water Heating Energy Efficiency						-		P				
4.2.2	Declaration of the Load Profile						-		-				
	Declared a load profile as described in Annex A						Tested as load profile S		P				
	Declared load profiles of 3XS, XXS, XS and S						-		N/A				
	3XS shall not exceed 7 litres in capacity						-		N/A				
	XXS and XS shall not exceed 15 litres in capacity						-		N/A				
	S shall not exceed 36 litres in capacity						30L		P				
AMD 4	For storage water heaters with declared load profile M,L,XL,XXL,3XL and 4XL, the requirements of mixed water At 40 °C shall be as illustrated in table below						-		-				
Declared Load Profile		M	L	XL	XXL	3XL	4XL	N/A					
Mixed Water at 40 °C		65 L	130 L	210 L	300 L	520 L	1040 L						
4.2.3	Minimum Energy Performance Standard(MEPS) for Water Heaters										-		
	The water heater MEPS values are presented in Table 1.					-					P		
	Table 1 – MINIMUM ENERGY EFFICIENCY ( $\eta_{wh}$ ) in %											Measured $\eta_{wh}$ 79.26%	
	Declared load profile		3XS	2XS	XS	S	M	L	XL	2XL	3XL		4XL
	Water heaters energy efficiency (with or without smart controls)		53	55	63	63	73	73	79	79	79		79
4.2.4	Minimum Energy Performance Standard (MEPS) for Hot Water Storage Tanks										-		
	Minimum energy performance standard (MEPS) requirements for hot water storage tanks with capacities higher or equal to 25 liters are based on the daily thermal losses QPR.						-				N/A		
	The limit values for QPR are expressed in table 2, rounded to 2 decimal places.						-				N/A		
4.2.5	Test Voltage						-				-		
AMD 4	The products shall be tested at 230V for single-phase, and shall be at 400V for three phase.						Applied 230V				P		

Test Report No	E-240333	Standard No:	SASO 2884
Clause	Requirement -Test	Result - Remark	Verdict

4.3	<b>Acceptance Criteria for Labelling and Market Surveillance</b>					-
	The energy label shall be accepted as valid when a sample unit(s) tested meets the following criteria:					-
	TABLE: <b>Acceptance Criteria for Labelling and Market Surveillance</b>					-
	Measured Point	Acceptance Criteria	Rated	Limit	Measured Value	Verdict
	a.) Tested Power (W)	$\geq 0.90 \times \text{rated power}$	1200W	1080W	1087W	P
	b) Tested Power (W)	$\leq 1.05 \times \text{rated power}$		1260W		
	c) Tested thermal losses (QPR)	$\leq 1.05 \text{ rated QPR, rated}$	-	-	-	N/A
	d) Tested Standing loss power (S)	$\leq 1.05 \text{ rated S}$	-	-	-	N/A
AMD 3	e.) Capacity (L)	$\geq 0.95 \times \text{rated Capacity}$	30L	$\geq 28.5L$	32L	P
	f.) Mixed quantity of water ( $V_{40}$ )	$\geq 0.97 \times \text{rated } V_{40}$	-	-	-	N/A
	g.) Tested Energy (any type)	$\leq 1.05 \times \text{rated annual energy}$	570kWh	$\leq 598.5kWh$	595kWh	P
	h) Tested Collector Aperture ( $m^2$ )	$\geq 0.98 \times \text{rated value}$	-	-	-	N/A
	i) Tested Standby Power $P_{sol;stby}$	$\leq 1.03 \text{ rated } P_{sol;stby}$	-	-	-	N/A
	j) Tested Pump power consumption $P_{sol;pump}$	$\leq 1.03 \text{ rated } P_{sol;pump}$	-	-	-	N/A
	Qelec	-	2.8	-	2.814kWh	-

6	<b>Marking and instructions</b>		
6.1	General information	-	-
	The following information <b>shall be marked on the nameplate</b> of the water-heater in English or Arabic and English	English	P
	The marking shall not be on a detachable part of the unit and shall be indelible, durable and easily legible	Durable	P
	Any information related to <b>energy performance</b> added on any part of the water heater unit or packaging shall not have any ambiguity or lead to misunderstanding of the performance of the unit	-	P
6.2	<b>Nameplate information</b>	-	-
	The nameplate information <b>shall include</b> , for conformity to this standard the following information:	-	-
	<ul style="list-style-type: none"><li>Manufacturer's name and/or trademark</li></ul>	NATIONAL HEATER FACTORY	P
	<ul style="list-style-type: none"><li>Country of origin</li></ul>	SAUDI ARABIA	P
	<ul style="list-style-type: none"><li>Manufacturer's model or type reference and serial number of the unit</li></ul>	NH L30V	P
	<ul style="list-style-type: none"><li>Rated voltage or rated voltage range in volts (V)</li></ul>	220V~	P
	<ul style="list-style-type: none"><li>Rated frequency in hertz (Hz)</li></ul>	60Hz	P
	<ul style="list-style-type: none"><li>Rated power input in Watt (W) or kiloWatts (kW)</li></ul>	1200W	P
	<ul style="list-style-type: none"><li>Rated Capacity</li></ul>	30L	P

Test Report No	E-240333	Standard No:	SASO 2884	
Clause	Requirement -Test		Result - Remark	Verdict

	<ul style="list-style-type: none"> <li>Annual standby losses (kWh/year) or daily standby losses (kWh/24h), when applicable</li> </ul>	-	N/A
6.3	<b>Instruction sheet</b>	-	-
	An instruction sheet or manual in both Arabic and English shall be delivered with each water heater	Instruction manual provided	P
	Tables, drawings and circuit diagrams may be depicted in English only	-	P
	The instruction sheet or manual shall include the following information as a minimum:	-	-
	a) Supplier's name or trade mark	National Heater Factory	P
	b) Supplier's model number	NH L30V	P
	c) Declared load profile	S	P
	d) Energy Efficiency Class of the model	D	P
	e) Water heating energy efficiency in %	83.46%	P
	f) Annual electricity consumption in kWh under average climatic condition for Saudi Arabia	570Kwh/y	P
	g) If applicable, other load profiles for which the water heater is suitable to use and the corresponding water heating energy efficiency and annual electricity consumption as set out in points (e) and (f)	-	N/A
	h) Thermostat temperature setting	Recommended 60°C	P
	i) specific precautions that shall be taken when the water heater is assembled, installed or maintained	See instruction manual	P
	j) Where Smart Control Compliance is declared as being enabled	-	N/A
	k) annual electricity consumption in kWh (or mass of butane equivalent when applicable)	-	N/A
	l) ) Collector aperture area in m <sup>2</sup>	-	N/A
	m) zero-loss efficiency	-	N/A
	n) First-order coefficient (W/(m <sup>2</sup> . K <sup>2</sup> ))	-	N/A
	o) Second-order coefficient (W/(m <sup>2</sup> . K <sup>2</sup> ))	-	N/A
	p) Incidence angle modifier (I <sub>am</sub> )	-	N/A
	q) Storage Capacity in Liters	30L	P
	r) pump power consumption in W	-	N/A
	s) standby power consumption in W,	-	N/A
	t) Annual non-solar heat contribution Q <sub>nonsol</sub> in KWh	-	N/A
	u) Annual auxiliary electricity consumption Q <sub>aux</sub>		
	In addition, for solar water heaters, the instruction sheet or manual shall include the following:	Electric storage water heater	-
	• The information specified in clause 6.2 and Table 6	-	N/A
	• Dimensions of the unit	-	N/A
	• Instruction for mounting and connection to the pipes	-	N/A
	• Instruction for connection to the electrical installation	-	N/A
	• Instructions necessary for the correct operation of the unit and any special precautions to be observed to ensure its safe use and maintenance	-	N/A
	• Instruction for packing and unpacking the unit	-	N/A
	• Instructions on unit handling and rigging	-	N/A
	• Net weight of the unit (empty)	-	N/A

Test Report No	E-240333	Standard No:	SASO 2884
Clause	Requirement -Test	Result - Remark	Verdict

<b>ANNEX C</b>	<b>Calculation of the Energy Efficiency</b>					
C.3	<b>Calculation of the Energy Efficiency Coefficient <math>\eta_{wh}</math></b>					
C3.1	<b>Conventional Water Heaters and HeatPump Water Heaters</b>					
$\eta_{WH} = \frac{Q_{ref}}{(Q_{fuel} + CC \cdot Q_{elec})(1 - SCF_{smart}) + Q_{cor}}$		$Q_{ref}$	$Q_{fuel}$	CC	$Q_{elec}$	SCF <sub>smart</sub>
		2.10	0	1.00	2.814	0
		$\eta_{wh} = 79.26\%$				
		$Q_{cor} = -0.16$				

C.5	<b>Determination of the Ambient Correction Term <math>Q_{cor}</math></b>					
(a) for conventional water heaters using electricity:		$Q_{elec}$	$Q_{fuel}$	$Q_{ref}$	SCF <sub>smart</sub>	CC
		2.814	0	2.10	0	1.00
$Q_{cor} = -k \cdot (CC \cdot (Q_{elec} \cdot (1 - SCF_{smart}) - Q_{ref}))$		$Q_{cor} = -0.16$				
Where the k values are given in Table C1 for each load profile		S				

C.6	<b>Determination of the mixed quantity of water <math>V_{40}</math></b>					
$V_{40} = V_{40;exp} \times \frac{(\theta_p - 15)}{(40 - 15)}$		The normalized value of the average temperature $\theta_p$				-
		Corresponds to the quantity of water delivered at least 40°C during test. $V_{40;exp}$				-
		$V_{40} = -$				N/A

ANNEX D	Calculation of the Annual Energy Consumption					
D.1	Principle for Calculation of the Annual Energy Consumption (AEC <sub>WH</sub> )			-	-	
	The annual energy is based on the energy efficiency ratio <b>AEC<sub>WH</sub></b> used for Classification and the reference energy Q <sub>ref</sub> used to characterize the water heaters.			595kWh/y	P	
D.2	Weather Data for Saudi Arabia			-	-	
	the following data are applied, in addition to the data used for test of the water heaters and water storage tanks (tables D1 and D2)			See table	P	
D.3	Calculation and Presentation of the Annual Energy Consumption (AEC <sub>WH</sub> )				-	
D.3.1	For Conventional Water Heaters				-	
$AEC_{WH} = 220 \times Q_{ref} / \eta_{wh;KSA}$			Q <sub>ref</sub>	$\eta_{wh;KSA}$	-	
			2.10	77.69%	-	
			AEC <sub>WH</sub> = 595kWh/y		-	
$\eta_{WH;KSA} = \frac{1}{1 + \left( \frac{1 - \eta_{WH}}{\eta_{WH}} \right) \times \left( \frac{65 - \vartheta_{amb;test}}{65 - \vartheta_{amb;KSA}} \right)}$			$\eta_{wh}$	$\vartheta_{amb;test}$	$\vartheta_{amb;KSA}$	-
			79.26%	20°C	24°C	-
			$\eta_{wh;KSA} = 77.69\%$			-
	Ambient temperature for test: $\vartheta_{amb;test} = 20^\circ C$			-	-	
	Ambient temperature for label: $\vartheta_{amb;KSA} = 24^\circ C$			-	-	

Remarks:

**NOTE:** No energy efficiency label provided.

Test Report No	E-240333	Standard No:	SASO 2884
Clause	Requirement -Test		Result - Remark
			Verdict

Photo no.1 (Marking)



Photo no.2 (General view / External package)





Test Report No	E-240333	Standard No:	SASO 2884
Clause	Requirement -Test		Result - Remark
			Verdict

Photo no.3 (Energy efficiency test report)



Report Reference E240333EEF55R03

### Storage Water Heater Test Data:









Applicable Standard(s)		SASO-2884:2017, BS EN 50440-2015		
Manufacturer	Country of Origin	Model	Type	Sub Type
NATIONAL HEATER FACTORY	SAUDI ARABIA	NH L30V	Electric	Storage
Test Start Date	Testing Stop Date	Load Profile	Rated Power	Actual Power
4/9/2024	4/10/2024	S	W	W
			1200	1087
Actual Capacity	Rated Capacity	T3	T5	Ambient
Litres	Litres	°C	°C	°C
32.00	30.00	61.28	52.65	20.10
				Smart
				0
				SCF
				1
$Q_{\text{testelec}}$	$Q_{\text{ref}}$	$Q_{\text{H2O}}$	$Q_{\text{elec}}$	$Q_{\text{cor}}$
kWh	kWh	kWh	kWh	kWh
2.54	2.10	2.14	2.814	-0.16
$V_{\text{full-drawing water}}$	CC	$\eta_{\text{elecwh}}$	$\eta_{\text{wh}}$	MEPS MIN. $\eta_{\text{wh}}$
Litres	Coefficient	%	%	%
54.10	1.00	74.63	79.26	63.00
$\eta_{\text{wh;KSA}}$	Rated AEC	Actual AEC	Actual AEC <sub>WH</sub>	Efficiency Class
%	kWh/y	kWh/y	kWh/y	
77.69	570	582	595	D

Photo no.4 (Classification as per declared load profile)

Table 3 – ENERGY EFFICIENCY CLASSIFICATION as per DECLARED LOAD PROFILE												
Energy Efficiency in %							79.26					
Bar Color	Energy Class		LOAD PROFILE									
			3XS	2XS	XS	S	M	L	XL	2XL	3XL	4XL
Dark Green	أ	A	95	100	105	105	210	300	300	300	300	300
Green	ب	B	87	89	97	97	140	160	160	160	160	180
Light Green	ج	C	77	79	87	87	93	95	98	110	110	110
Yellow	د	D	69	71	79	79	87	87	92	93	93	93
Orange	هـ	E	61	63	71	71	80	80	86	86	86	86
Red	و	F	53	55	63	63	73	73	79	79	79	79
Dark Red	ز	G	45	47	55	55	65	65	71	71	71	71

Test Report No	E-240333	Standard No:	SASO 2884
Clause	Requirement -Test	Result - Remark	Verdict

Conformity Decision is usually included in the report, unless the agreement states otherwise by the client.

Results Notes: The acceptance criterion is based on :		A-The relevant TR Requirements <input type="checkbox"/>	B-The relevant standard specifications <input type="checkbox"/>	
		C- Manufacturer's manual (product technical data sheet) <input type="checkbox"/>	D- Customer requirements <input type="checkbox"/>	
Acceptance Rule is based on:		Special Case	Rejection Rule (Failing)is based on:	
A- The measured value (+) measurement uncertainty value is less than the maximum required to criteria of acceptance. B- The measured value (-) measurement uncertainty value is greater than the minimum required to criteria of acceptance.		May be accept if: Measured result $\leq$ the upper limit Measured result $\geq$ lower limit May be rejected if : measured value < the upper limit measured result > lower limit	Reject when a confidence level of less than 95% is acceptable A- The measured value (+) measurement uncertainty value is greater than the maximum required to criteria of acceptance. B- The measured value (-) measurement uncertainty value is less than the minimum required to criteria of acceptance.	
				
				
♦ = measurement result with agreed method			I = uncertainty interval of agreed method	

Notes on results: The acceptance criterion is based on; A-Relevant standard specification ☐  
B-Manufacturer's manual (product technical data sheet) ☐ C-Customer requirements . ☒

The rule of acceptance is based on: The measured value fulfills the requirement according to the acceptance criterion, taking into account the uncertainty value in the measurement

The rule of rejection is based on: The measured value does not achieve the required according to the acceptance criterion, taking into account the uncertainty value in the measurement

☒ The sample passed all the above-mentioned tests in accordance with the requirements of the product

☐ The sample passed all the tests mentioned above in accordance with the requirements for the product, except for the ..... test where the measured value does not meet the requirements of the product mentioned in the attached standard specifications.

The result is for the sample referred to in the report, which has been tested only and is only representative of itself.

Accreditation statues :

All tests are accredit : ☐

All tests are accredit except:

REMARK :

SOFT COPY OF THE CONTROL TEST RESULT SHEET IS AUDITED BY THE LAB SUPERVISOR

Name	Inspected by	Lab supervisor/ Reviewer	Technical Manager
Sign	Rieman capio	Patrick perea	Ahmad awad
Date	15 /4 / 2024	15 /4 / 2024	15 / 4 / 2024

"End of Report"

